

Unenclosed Vertical Platform Lift

VPL-UL for Commercial Applications



Available with:

- Accelerated Acme Screw Drive at 20 fpm
- Full-speed battery backup

Proudly Made in the U.S.A. 

Convenient access to all levels

For commercial, outdoor or indoor use, Symmetry Vertical Platform Lifts (VPLs) help eliminate the barrier that stairs may present for people with limited mobility. VPLs provide convenient access without compromising architectural character. Designed and manufactured to comply with ASME A18.1, ICC A117.1, and NFPA 70.

This brochure is intended for INFORMATIONAL PURPOSES ONLY and SHOULD NOT be used for construction.

Standard Features

- Rated Capacity: 750 lbs.
- Speed: 10-20 fpm (see drive options for details)
- Lifting Height: Up to 60"
- Steel construction with powder-coated finish
- A.W.A.R.E. system (Active Wiring, Accessories, Relay and Electronics Diagnosis)*
- Constant-pressure up/down control switch installed on the platform
- Constant-pressure control station provided at each landing
- Manual lowering device
- Warranty: Four-year limited parts

Safety Features

- Grab rail
- Non-skid platform surface (Black)
- Obstruction safety panel under platform
- Alarm and emergency stop switch
- Landing interlocks keep doors closed/locked when the platform is at another landing
- Upper final limit switch (optional on Hydraulic Drive)
- Safety lift nut for Acme Screw Drive
- Broken chain safeties for Hydraulic Drive

Optional Features

- Remote mounted controller
- 230 VAC power supply
- ADA phone for both indoor or outdoor applications
- Emergency platform lighting
- Full-speed battery backup
- 5 ftc LED lights with or without battery backup
- Power gate/door operators
- Stationary or flip-up ramp
- Key switches to disable platform and/or landing controls
- Extreme weather package

Clear Platform Sizes

Custom sizes and designs available

- 36"W x 54"L
- 36"W x 60"L
- 36"W x 48"L
- 42"W x 60"L

Enter/Exit Configurations

- Straight-Through
- 90°
- 3 Openings

Gate/Door Options

- 42" platform gate**
- 42" landing gate**
- 80" landing gate**
- Non-Fire-rated Red Oak door†
- 1½ hour Fire-rated steel door (B-Label)

Drive Options



- Acme Screw Drive: 10 fpm, 1.5 HP, 115 VAC
- Accelerated Acme Screw Drive: 20 fpm, 1.5 HP, 115 VAC
- Chain Hydraulic Drive: 17-20 fpm, 3 HP, 115 VAC

Straight-Through Configuration with Pit				
Clear Platform (W" x L")	Equipment Width	Equipment Length	Finished Width (1)	Finished Length (2)
36" x 48"	51¾"	49¾"	53¾"	51¼"
36" x 54"	51¾"	55¾"	53¾"	57¼"
36" x 60"	51¾"	61¾"	53¾"	63¼"
42" x 60"	57¾"	61¾"	59¾"	63¼"
90° Configuration with Pit				
42" x 60"	55¾"	63"	57"	66¼"

- (1) If platform gate is hinged opposite the main tower and a mid-mount gate operator is used, add ½" to this dimension.
 (2) A flip-up ramp will add 14¼" to finished length. A stationary ramp will add 25" to finished length.

Straight-Through Footprint Layout

See VPL Design Guide for additional configurations



Color Options

Full selection of RAL colors available



- * Symmetry Elevating Solutions exclusive
- ** Available with optional Clear or Bronze acrylic insert
- † Also available in other wood choices by request

Colors illustrated may vary due to print or digital technology